Dane aktualne na dzień: 30-10-2026 01:24

Link do produktu: https://www.strefainternetowa.com/obejma-urgu-6-m8x100mm-kolek-rura-159-168-p-931.html

OBEJMA URGU 6'' M8X100MM +KOŁEK (RURA 159-168)

Cena	**14,89 zł**
Numer katalogowy	**ALP-18766427450**
Kod producenta	**URG6**
Kod EAN	**5907527913088**

Opis produktu

Stalowy uchwyt do rur

Stalowy uchwyt do mocowania i podparcia przewodów z rur.

Wymiary : 159-168mm 6 cali

Składają się z :

- półobejmy stałej ze zgrzewaną nakrętką
- półobejmy ruchomej
- wkrętów z łbem walcowym z nacięciem krzyżowym
- łącznika tworzywowo-metalowego z trzpieniem dwugwintowym, którego jeden koniec wkręcany jest w tuleję tworzywową, a drugi w nakrętkę połączoną z obejmą stałą
- nakrętki M8 do półobejmy stałej
- podkładki z PVC eliminującej drgania

Uchwyty pokryte są powłąką cynku galwanicznego

Uchwyty mogą być stosowane do mocowania przewodów z rur instalacyjnych centralnego ogrzewania, ciepłej i zimnej wody, kanalizacyjnych, gazowych, oraz rur odpływowych wody opadowej i rur wentylacyjnych.

Uchwyty mogą być mocowane do pełnych podłoży budowlanych wykonanych z :

- betonu zwykłego o wytrzymałości na ściskanie min. 15MPa
- cegły ceramicznej pełnej o wytrzymałości na ściaskanie min 12Mpa
- cegły wapienno-piaskowej o pełnej wytrzymałości na ściskanie min. 12MPa
- betonu komórkowego o wytrzymałości na ściskanie min. 3MPa

Montaż w podłożu któego temperatura w czasie eksploatacji zawierać się będzie w zakresie -20°C do 40°C

Zakres temperatur podtrzymywanej rury to -25°C do 80°C

Uchwyty mogą być stosowane w pomieszczeniach narażonych na działanie czynników korozyjnych.

Aprobata techniczna AT-15-8113/2009

Parametry produktu

- **Stan:** Nowy
- **Kod producenta:** URG6
- **Marka:** Stalco
- **Typ:** kształtka
- **Rodzaj:** uchwyt
- **Materiał wykonania:** stal
- **Kod taryfy celnej:** 74122000
- **EAN (GTIN):** 5907527913088

Informacje o bezpieczeństwie

List of pipe and fitting safety warnings based on the requirements of General Product Safety Regulation (EU) 2023/988 (GPSR): * Material selection: Make sure that the selected pipes and fittings are suitable for the type of substance being transported (drinking water, wastewater, chemicals). * Temperature and pressure: Verify that the pipes and fittings are rated for maximum temperature and operating pressure in the installation. * Compatibility: Ensure that pipe and fitting materials are compatible with other installation components (e.g. gaskets, threads, adhesives). * Assembly: Follow the manufacturer's installation instructions, use the appropriate tools and techniques to avoid damage and leaks. * Tightness: Before starting the installation, check the tightness of the joints to prevent leaks. * Freezing protection: Protect pipes from freezing, especially in areas exposed to low temperatures. * Protection against damage: Avoid exposing pipes to impact, mechanical stress, or contact with sharp objects that can damage their structure. * Regular inspections: Periodically check the condition of pipes and fittings for signs of corrosion, cracks, or other damage. * Replacement of damaged components: Replace damaged pipes and fittings immediately to prevent breakdowns and leaks. * Work safety: When cutting and installing pipes, use appropriate personal protective equipment (e.g. safety glasses, gloves). * Disposal: Dispose of used or damaged pipes and fittings in accordance with applicable environmental regulations. * Availability: Provide easy access to pipes and fittings for inspection and possible repairs. * Markings: Keep clear markings on pipes and fittings to easily identify their type and parameters. * Storage: Store pipes and fittings in a dry, shaded place, away from heat sources and direct sunlight. * Fire safety: For pipes and fittings made of flammable materials, ensure proper fire protection. * Kids: Keep pipes and fittings out of reach of children to avoid the risk of swallowing small items or injuries.

Producent — dane kontaktowe

STALCO Sp. z o.o. Sp.k.
ul. Krakowska 145
32-050
Skawina
PL
centrala@stalco.pl