Dane aktualne na dzień: 14-11-2026 03:00

Link do produktu: https://www.strefainternetowa.com/przylacze-z-gwintem-wewnetrznym-12-3-4-exp-stalco-garden-s101010257-p-2920.html



Przyłącze z gwintem wewnętrznym 1/2"-3,4" EXP Stalco GARDEN S101010257

Cena	**8,00 zł**
Numer katalogowy	**ALP-17146591550**
Kod producenta	**S101010257**
Kod EAN	**5905947900657**

Opis produktu

Przyłącze z gwintem wewnętrznym 1/2"-3,4" EXP Stalco GARDEN S101010257

Przyłącze z gwintem wewnętrznym 1/2"-3,4" EXP Stalco GARDEN S101010257

Przyłącze z gwintem wewnętrznym EXP z redukcją 1/2"-3/4" S101010257

Przyłącze z gwintem wewnętrznym EXP to praktyczny element, który umożliwia elastyczne połączenie różnych elementów systemu nawadniania ogrodu.

- **Materiały:** Wykonane z ABS i TPR, co zapewnia trwałość, odporność na warunki atmosferyczne oraz elastyczność podczas użytkowania.
- **Przyłącze z redukcją:** Posiada przyłącze z redukcją, umożliwiające połączenie z innymi elementami systemu o różnych średnicach, **1/2" -3/4".**
- **Kompatybilność z innymi markami:** Dzięki funkcji "fits with other brands", przyłącze jest kompatybilne z różnymi innymi markami, co pozwala na uniwersalne zastosowanie i dopasowanie do różnych systemów nawadniania.

Przyłącze z gwintem wewnętrznym EXP to niezbędny element dla ogrodników, który zapewnia łatwe i stabilne połączenie różnych elementów systemu nawadniania ogrodu, przy jednoczesnym zachowaniu trwałości i elastyczności.

Producent: STALCO SPÓŁKA Z OGRANICZONĄ ODPOWIEDZIAL

EAN: 5905947900657

WAGA: 0

Parametry produktu

- **Stan:** Nowy
- **Kod producenta:** S101010257

- **Marka:** Stalco
- **Rodzaj:** przyłącze
- **Waga produktu z opakowaniem jednostkowym:** 0.027
- **Kod taryfy celnej:** 84249080
- **EAN (GTIN):** 5905947900657

Informacje o bezpieczeństwie

List of safety warnings for fittings and terminals based on the requirements of General Product Safety Regulation (EU) 2023/988 (GPSR): 1. Check compatibility: Make sure the fittings and tips are compatible with the irrigation system I am using. Incorrect fit can lead to leaks or breakdowns. 2. Condition Inspection: Regularly inspect fittings and tips for damage, cracks, or wear. Damaged components can cause leaks or sudden disconnection. 3. Suitable installation: Mount the fittings and tips according to the manufacturer's instructions, using the appropriate tools. Too strong or too weak tightening can damage components or cause leaks. 4. Avoid overloads: Do not exceed the maximum working pressure of fittings and tips. Overload can lead to their damage or disconnection, posing a threat to people in the vicinity. 5. Protect against frost: If fittings and tips are exposed to frost, make sure the irrigation system is properly protected against freezing. Freezing water can damage the fittings, leading to leaks. 6. Sun protection: Long-term sun exposure can weaken the material of fittings and tips. If possible, protect the components from direct UV rays. 7. Safe storage: Store fittings and tips in a dry and cool place, away from children and pets. 8. Disposal: Dispose of worn or damaged fittings and tips in accordance with local environmental regulations. Improper disposal can contaminate soil or water. 9. Caution with chemicals: Avoid contact of fittings and tips with aggressive chemicals that can damage the material. Use only the measures recommended by the manufacturer. 10. Connection protection: Make sure all connections are tight and stable to avoid accidentally disconnecting the irrigation system.

Producent — dane kontaktowe

STALCO
Ofiar Katynia 1
32-050
SKAWINA
PL
centrala@stalco.pl
696113253