Dane aktualne na dzień: 27-10-2026 12:34

Link do produktu: https://www.strefainternetowa.com/stalco-tasma-malarska-washi-38-x-25-m-p-1721.html

STALCO TAŚMA MALARSKA WASHI 38 x 25 m

Cena	**13,99 zł**
Numer katalogowy	**ALP-18154606944**
Kod producenta	**38220**
Kod EAN	**5905947951017**

Opis produktu

Stalco Taśma malarska Washi uniwersalna 38mm x 25m S042138220

Taśma malarska Washi uniwersalna — taśma z papieru washi przeznaczona do wszechstronnych prac malarskich i ogólnobudowlanych. Pewnie przylega do różnych powierzchni, a po zakończeniu prac odrywa się czysto, bez śladów kleju. Wytrzymała struktura papieru washi z hydrofobową powłoką pomaga uzyskać ostre, równe krawędzie i skutecznie zabezpieczać powierzchnie. Jest odporna na promieniowanie UV i wilgoć.

CECHY I ZALETY:

- Kompatybilna z farbami emulsyjnymi, lateksowymi, ceramicznymi, olejnymi, ftalowymi oraz lakierami
- Pewna przyczepność do powierzchni gładkich i lekko chropowatych: drewno, metal, plastik, tynki, gładzie, cegła
- Łatwe usuwanie do 30 dni wewnątrz i do 30 dni na zewnątrz budynku
- Czyste odrywanie — nie pozostawia kleju
- Odporność na temperaturę do 130 ℃
- Skala przyczepności do podłoża: 3/5

DANE TECHNICZNE:

- Rodzaj kleju: akrylowy
- Materiał: papier washi
- Grubość(um): 100±10
- Początkowa lepkość (#): 12-14
- Siła odrywania 180 °(N/25MM): 2,2-3,0
- Wydłużenie (%/10mm): 5,4-5,7
- Wytrzymałość na rozciąganie (N/10MM): 35-48
- Odporność na temperaturę (℃): 130℃

Parametry produktu

- **Stan:** Nowy
- **Kod producenta:** 38220
- **Marka:** Stalco
- **Długość:** 25
- **Szerokość:** 38

- **Przeznaczenie:** wewnątrz budynku
- **Kolor:** żółty
- **Waga produktu z opakowaniem jednostkowym:** 0.1
- **EAN (GTIN):** 5905947951017

Informacje o bezpieczeństwie

List of safety warnings for assembly tapes based on the requirements of Regulation (EU) 2023/988 on general product safety (GPSR): 1. Risk of falling: Make sure that the surface on which you stick the tape is clean and dry. Improper surface preparation can lead to weakened adhesion and fall of fixed objects. 2. Load: Do not exceed the maximum load of the belt. Overloading the tape can cause it to break and damage the attached objects. 3. Weather conditions: Avoid using tapes in extreme weather conditions (high humidity, extreme temperatures). They can affect the effectiveness of gluing. 4. Surface Material: Check that the tape is suitable for the material on which it is to be used. Some materials can react with the adhesive, causing damage. 5. Application: Apply the tape evenly, avoiding air bubbles and creases. Incorrect application can reduce the adhesive strength. 6. Disassembly: Disassembly of the tape can damage the surface. Always carefully remove the tape, following the manufacturer's instructions to avoid damage. 7. Kids: Keep the tape out of reach of children. There is a risk of swallowing small parts. 8. Skin contact: Avoid prolonged contact of the adhesive with the skin. This can cause irritation. 9. Storage: Store the tape in a dry and cool place, away from direct sunlight, to prevent loss of adhesive properties. 10. Testing: Before full assembly, test the tape on a small, invisible area to make sure it does not cause surface damage.

Producent — dane kontaktowe

STALCO
Ofiar Katynia 1
32-050
SKAWINA
PL
centrala@stalco.pl
696113253