Dane aktualne na dzień: 27-10-2026 11:40

Link do produktu: https://www.strefainternetowa.com/tasma-bitumiczna-eurovent-fixbit-cegla-300mmx10mb-p-2171.html

TAŚMA BITUMICZNA EUROVENT FIXBIT cegła 300mmx10mb

Cena	**150,00 zł**
Numer katalogowy	**ALP-17900755087**
Kod producenta	**Fixbit 300 8004**
Kod EAN	**5905090709466**

Opis produktu

TAŚMA BITUMICZNA

FIXBIT 300mm x 10mb

KOLOR / CEGŁA

Taśma bitumiczna Eurovent® FIXBIT, aluminiowa taśma reperacyjna na podłożu bitumicznym, służąca do sklejania i uszczelniania obróbek dekarskich w obszarach dachów płaskich i skośnych. Dostępna w kilku wersjach kolorystycznych. Wykonana na bazie bitumu, bezrozpuszczalnikowa taśma z warstwą aluminium i oddzielającym papierem silikonowym.

Zalety:

- Posiada dużą siłę klejenia
- Bezrozpuszczalnikowa
- Wodoszczelna

ODPORNOŚĆ NA UV

odporny

MATERIAŁ

bitum, aluminium

ROZMIAR

300 mm x 10 mb

TEMPERATURA KLEJENIA

od 5°C do 35°C

FIXBIT

Taśma bitumiczna Eurovent® FIXBIT znajduje zastosowanie przy sklejaniu i uszczelnianiu obróbek dekarskich w obszarach komina, okien dachowych, ogniomurach, świetlikach, koszach dachowych i elementach wentylacyjnych dachów płaskich i skośnych. Idealnie łączy wszelkiego rodzaju elementy metalowe z innymi tworzywami sztucznymi, betonem oraz cegłą.

Parametry produktu

- **Stan:** Nowy
- **EAN (GTIN):** 5905090709466
- **Kod producenta:** Fixbit 300 8004
- **Marka:** Eurovent
- **Typ akcesoriów:** taśma
- **Rodzaj taśmy:** bitumiczna
- **Waga produktu z opakowaniem jednostkowym:** 2

Informacje o bezpieczeństwie

List of safety warnings for assembly tapes based on the requirements of Regulation (EU) 2023/988 on General Product Safety (GPSR): 1. Risk of falling: Make sure that the surface on which you stick the tape is clean and dry. Improper surface preparation can lead to weakened adhesion and fall of fixed objects. 2. Load: Do not exceed the maximum load of the belt. Overloading the tape can cause it to break and damage the attached objects. 3. Weather conditions: Avoid using tapes in extreme weather conditions (high humidity, extreme temperatures). They can affect the effectiveness of gluing. 4. Surface material: Check that the tape is suitable for the material on which it is to be used. Some materials can react with the adhesive, causing damage. 5. Application: Apply the tape evenly, avoiding air bubbles and creases. Incorrect application can reduce the adhesive strength. 6. Disassembly: Disassembly of the tape can damage the surface. Always carefully remove the tape, following the manufacturer's recommendations to avoid damage. 7. Kids: Keep the tape out of reach of children. There is a risk of swallowing small parts. 8. Skin contact: Avoid prolonged contact of the adhesive with the skin. This can cause irritation. 9. Storage: Store the tape in a dry and cool place, away from direct sunlight, to prevent loss of adhesive properties. 10. Testing: Before full assembly, test the tape on a small, invisible area to make sure it does not cause surface damage.

Producent — dane kontaktowe

Eurovent Sp. z o.o.
ul. Ogrodowa 31
62-069
Dąbrówka
PL
office@eurosystempolska.pl